

JLA 16/98

Washer/Dryer Stack System



The JLA 16/98 Stack System combines a high speed spin, free-standing washing machine and JLA 98 dryer which fit into the space of a single machine, making them ideal for installations where space is at a premium.

The washer complies with all healthcare guidelines and water regulations, whilst the dryer is one of the most efficient on the market, both in terms of drying ability and energy usage.



WRAS
Approved



OTEX
Ready



Thermal
Disinfection



Sluice Cycle
Options



SMART
Technology



JLA 16/98

Washer/Dryer Stack System

Key Features

Washer

- ✦ JLA Sense absorption technology.
- ✦ Built-in Type 'A' air gap complies with relevant water regulations.
- ✦ Microprocessor controls for easy use.
- ✦ Free-standing for lower installation costs.
- ✦ 1,000rpm super spin reduces drying time by up to 30%. Standard spin speed for delicates.
- ✦ Two sluice programmes for both thermal and chemical disinfection.
- ✦ Liquid-feed detergent option.
- ✦ OTEX ready.

Dryer

- ✦ Stylish and robust.
- ✦ Fast-dry cycles ensure low running costs.
- ✦ Easy to use with touch control pad and four temperature settings.
- ✦ Wide door opening for easy loading and unloading.
- ✦ Gas or electric heat.

Specification

Details (combined)

JLA 16/98 Stack System	
Height (mm)	1920
Width (mm)	683
Depth (mm)	796
Net Weight (Kg)	279

Details (individual machines)

	JLA 16 Washer	JLA 98 Dryer
Capacity (Kg/lb)	7.5/16	9/20
Drum Volume (ltr)	73	201
G.Force low spin/fast spin (Gs)	83/144	-
Microprocessor Control	✓	✓
Free-standing	✓	✓
Gas Rating kW (Btu/hr)	-	5.9 (20,000)
Connection Size ("BSP)	-	3/8
No. of Water Connections (cold/hot)	2/1	-
Size ("BSP)	3/4	-
Exhaust (mm Ø)	-	102
Make-Up Air m ² (in ²)	-	0.013 (20)
Airflow m ² (ft ³ /min)	-	5.1 (180)
Drain Connection (mm Ø)*	50	-
Electric Dryer (Volt/ph/Amp)	230/1/25	230/1/25
Gas Dryer (Volt/ph/Amp)	230/1/10	230/1/10
Self Heat Washer 9kW (Volt/ph/Amp)	230/1/45	230/1/45
Self Heat Washer 6kW (Volt/ph/Amp)	230/1/32	230/1/32
Self Heat Washer 9kW (Volt/ph/Amp) (per phase)	400/3/20	400/3/20

All specifications subject to change without notice.

For full specification refer to the 'installation specification sheet'.

NOTE: A stack unit requires 2 electrical supplies.

* Machines are supplied as standard with 2 drain connections at 80mm and 155mm high. These are maximum heights with the levelling feet in place.



Please refer to SMART Wash brochure for full details of JLA16 SMART Wash.

Find out more about our full range of products and services

JLA Commercial Laundry

0800 591 903

ROI 01601 0525

info@jla.com jla.com